


PRODUCT TECHNICAL SPECIFICATION

CORAL VITRO – **CV1500RB**

FCP\_039\_03\_EN-01



**DESCRIPTION:**

Tank for domestic hot water (DHW) **STORAGE**.

For vertical installation on floor. Manufactured in **VITREOUS ENAMELLED STEEL** according to the DIN4753 standard, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Cathodic protection based on magnesium anodes.

Equipped with DN400 side manhole for inspection / cleaning tasks, or optionally, for the installation of a stainless steel plate to allocate electric heating elements.

**MAIN CHARACTERISTICS**

Total capacity:	Total	1500	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	ww: DHW outlet	2	" M
	kw: cold water inlet	2	" M
	e: drain	1 ½	" M
	z: recirculation	1 ½	" H
	s: side connection	2	" M
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	169	W
External dimensions:	D: Diameter	1160	mm
	H: Height (without connections)	2320	mm
	Diagonal (without connections)	2593	mm
Packaging dimensions:	Width / Height	1160 x 2320	mm
Weight:	Without packaging / With packaging	369 / 369.5	kg