




PRODUCT TECHNICAL SPECIFICATION  
GEISER INOX – **GX800RB**

FCP\_010\_01\_EN



**DESCRIPTION:**

Tank for domestic hot water (DHW) **STORAGE**. For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. The removable insulation system allows the tank to access through 800 mm wide doors.

Equipped with DN400 side manhole for inspection / cleaning tasks, or optionally, for the installation of a stainless steel plate to allocate electric heating elements.

Includes sensor pocket on upper connections plate and "S" control panel (thermometer).

**MAIN CHARACTERISTICS**

Total capacity:	Total	800	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	ww: DHW outlet	1 ½	" M
	kw/e: cold water inlet / drain	1 ¼	" M
	z: recirculation	1 ½	" M
	m: plate exchanger connection	1 ½	" M
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	95	W
External dimensions:	D: Diameter	950	mm
	H: Height (without connections)	1840	mm
	Diagonal (without connections)	2071	mm
Packaging dimensions:	Width / Height	1000 x 1030 / 2040	mm
Weight:	Without packaging / With packaging	184 / 206	kg