



PRODUCT TECHNICAL SPECIFICATION
GEISER INOX – **GX150TSC**

FCP_011_02_EN



DESCRIPTION:

Tank for domestic hot water (DHW) **STORAGE-PRODUCTION.**

For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid PU thermal insulation and external PVC lining with zip closure. Tank includes an internal **COIL** made of stainless steel AISI 316 for thermal exchange.

Connections are placed at the top, to allow the installation of the tank below a boiler.

Equipped with top opening for inspection / cleaning tasks.

Includes sensor pocket on upper connections plate and thermometer on top cover.

MAIN CHARACTERISTICS

Total capacity:	Total / DHW Tank	148	L
Maximum working pressure:	Primary / Secondary	25 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	Coil	1.3	m ²
Connections:	kv: primary inlet	¾	" M
	kr: primary outlet	¾	" M
	ww: DHW outlet	¾	" M
	kw: cold water inlet	¾	" M
	e: drain	½	" F
	z: recirculation	¾	" M
	Energy efficiency:	ErP Class	A
Static heat losses acc. to EN12897		---	W
External dimensions:	D: Width / depth	510	mm
	H: Height (without connections)	1210	mm
	Diagonal (without connections)	1314	mm
Packaging dimensions:	Width / Height	680 / 1450	mm
Weight:	Without packaging / With packaging	47 / -	kg