



PRODUCT TECHNICAL SPECIFICATION  
GEISER INOX – **GX6D190**

FCP\_04\_03\_EN



**DESCRIPTION:**

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical wall mounting or installation on floor, in vertical or in horizontal position (optional\*). Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Equipped with side opening in primary circuit for an optional electric heating element.

Tank includes brackets for wall mounting, sensor pocket on the upper connections plate and “K” control panel (factory wired and mounted; with thermometer, double regulation and safety thermostat, winter-summer switch and indicator LEDs).

**MAIN CHARACTERISTICS**

Total capacity:	Total / DHW Tank	191 / 150	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	1.2	m <sup>2</sup>
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	58	W
External dimensions:	D: Diameter	620	mm
	H: Height (without connections)	985	mm
	Diagonal (without connections)	1164	mm
Packaging dimensions:	Width / Height	680 / 1190	mm
Weight:	Without packaging / With packaging	52 / 61	kg

(\*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.

**Lapesa Grupo Empresarial, S.L.**

Pol. Industrial Malpica, Calle A, Parc. 1-A \* ES-50016 ZARAGOZA (ESPAÑA)  
Tel.: +34 976 465 180 / Fax: +34 976 574 393 \* e-mail: lapesa@lapesa.es

