


PRODUCT TECHNICAL SPECIFICATION
GEISER INOX – GX6D600

FCP_04_06_EN



DESCRIPTION:

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For floor installation, in vertical or in horizontal position (optional*). Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Equipped with side opening in primary circuit for an optional electric heating element.

Includes sensor pocket on the upper connections plate and “**K**” control panel (factory wired and mounted; with thermometer, double regulation and safety thermostat, winter-summer switch and indicator LEDs).

MAIN CHARACTERISTICS

Total capacity:	Total / DHW Tank	608 / 500	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	3.0	m ²
Connections:	kv: primary inlet	1 ½	" F
	kr: primary outlet	1 ½	" F
	ww: DHW outlet	1	" M
	kw: cold water inlet / drain	1	" M
	z: recirculation	1	" M
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	103	W
External dimensions:	D: Diameter	770	mm
	H: Height (without connections)	1730	mm
	Diagonal (without connections)	1894	mm
Packaging dimensions:	Width / Height	820 / 1920	mm
Weight:	Without packaging / With packaging	147 / 158	kg

(*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.