


PRODUCT TECHNICAL SPECIFICATION  
 GEISER INOX – **GX6D90**

FCP\_04\_01\_EN



**DESCRIPTION:**

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION.**

For vertical wall mounting or installation on floor, in vertical or in horizontal position (optional\*). Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Equipped with side opening in primary circuit for an optional electric heating element.

Tank includes brackets for wall mounting, sensor pocket on the upper connections plate and “K” control panel (factory wired and mounted; with thermometer, double regulation and safety thermostat, winter-summer switch and indicator LEDs).

**MAIN CHARACTERISTICS**

Total capacity:	Total / DHW Tank	82 / 62	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	0.8	m <sup>2</sup>
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	45	W
External dimensions:	D: Diameter	480	mm
	H: Height (without connections)	750	mm
	Diagonal (without connections)	890	mm
Packaging dimensions:	Width / Height	500 / 970	mm
Weight:	Without packaging / With packaging	35 / 40	kg

(\*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.

**Lapesa Grupo Empresarial, S.L.**

Pol. Industrial Malpica, Calle A, Parc. 1-A \* ES-50016 ZARAGOZA (ESPAÑA)  
 Tel.: +34 976 465 180 / Fax: +34 976 574 393 \* e-mail: lapesa@lapesa.es

