


PRODUCT TECHNICAL SPECIFICATION
GEISER INOX – **GX6DE600**

FCP_06_06_EN



DESCRIPTION:

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure.

Equipped with side threaded connection in primary circuit to allocate an optional electric heating element.

Includes sensor pocket on the upper connections plate and “**K**” control panel (factory wired and mounted; with thermometer, double regulation and safety thermostat, winter-summer switch and indicator LEDs).

MAIN CHARACTERISTICS

| | | | |
|------------------------------|------------------------------------|------------|----------------|
| Total capacity: | Total / DHW Tank | 608 / 433 | L |
| Maximum working pressure: | Primary / Secondary | 3 / 8 | bar |
| Maximum working temperature: | Primary / Secondary | 110 / 90 | °C |
| Exchange surface: | DHW tank wall | 2.8 | m ² |
| Connections: | kv: primary inlet | 1 ½ | " F |
| | kr: primary outlet | 1 ½ | " F |
| | ww: DHW outlet | 1 | " M |
| | kw: cold water inlet / drain | 1 | " M |
| | z: recirculation | 1 | " M |
| | R: connection for electric element | 2 | " F |
| | N: primary side connection | 1 ½ | " F |
| Energy efficiency: | M: primary side connection | 1 ½ | " F |
| | ErP Class | C | |
| External dimensions: | Static heat losses acc. to EN12897 | 103 | W |
| | D: Diameter | 770 | mm |
| | H: Height (without connections) | 1730 | mm |
| Packaging dimensions: | Diagonal (without connections) | 1894 | mm |
| | Width / Height | 790 / 2000 | mm |
| Weight: | Without packaging / With packaging | 90 / 98 | kg |