




PRODUCT TECHNICAL SPECIFICATION  
GEISER INOX – **GX6DEC190**

FCP\_05\_03\_EN



**DESCRIPTION:**

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical wall mounting or installation on floor, in vertical or in horizontal position (optional\*). Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Equipped with side inspection opening in primary circuit, with factory-mounted flanged electric heating element.

Tank includes brackets for wall mounting, sensor pocket on the upper connections plate and “K” control panel (factory wired and mounted; with thermometer, double regulation and safety thermostat, winter-summer switch and indicator LEDs).

**MAIN CHARACTERISTICS**

Total capacity:	Total / DHW Tank	191 / 150	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	1.2	m <sup>2</sup>
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
Electric element (as standard):		2.2	kW
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	58	W
External dimensions:	D: Diameter	620	mm
	H: Height (without connections)	985	mm
	Diagonal (without connections)	1164	mm
Packaging dimensions:	Width / Height	680 / 1190	mm
Weight:	Without packaging / With packaging	52 / 61	kg

(\*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.