


PRODUCT TECHNICAL SPECIFICATION  
GEISER INOX – **GX6PAC300**

FCP\_08\_01\_EN



**DESCRIPTION:**

“DOUBLE WALL” tank for domestic hot water (DHW) **STORAGE-PRODUCTION.**

For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure.

Equipped with side threaded connection in primary circuit to allocate an optional electric heating element. Includes sensor pocket on upper connections plate and “S” control panel (thermometer).

**MAIN CHARACTERISTICS**

Total capacity:	Total / DHW Tank	244 / 116	L
Maximum working pressure:	Primary (tank) / Secondary	3 / 8	bar
Maximum working temperature:	Primary (tank) / Secondary	110 / 90	°C
Connections:	ww: DHW outlet	¾	“ M
	kw: cold water inlet / drain	¾	“ M
	z: recirculation	¾	“ M
	R: connection for electric element	2	“ F
	eh: side connection	1 ¼	“ F
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	62	W
External dimensions:	D: Diameter	560	mm
	H: Height (without connections)	1770	mm
	Diagonal (without connections)	1856	mm
Packaging dimensions:	Width / Height	680 / 1940	mm
Weight:	Without packaging / With packaging	78.2 / 82	kg