



PRODUCT TECHNICAL SPECIFICATION
GEISER INOX – **GX6PAC800**

FCP_08_04_EN



DESCRIPTION:

"DOUBLE WALL" tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. The removable insulation system allows the tank to access through 800 mm wide doors. Equipped with side threaded connection in primary circuit to allocate an optional electric heating element.

Includes sensor pocket on upper connections plate and "S" control panel (thermometer).

MAIN CHARACTERISTICS

Total capacity:	Total / DHW Tank	770 / 200	L
Maximum working pressure:	Primary (tank) / Secondary	3 / 8	bar
Maximum working temperature:	Primary (tank) / Secondary	110 / 90	°C
Connections:	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
	R: connection for electric element	2	" F
	eh: side connection	1 ¼	" F
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	87	W
External dimensions:	D: Diameter	950	mm
	H: Height (without connections)	1840	mm
	Diagonal (without connections)	2070	mm
Packaging dimensions:	Width / Height	1030 x 1000 / 2040	mm
Weight:	Without packaging / With packaging	150 / 175	kg