



PRODUCT TECHNICAL SPECIFICATION
GEISER INOX – **GX6S130**

FCP_01_02_EN



DESCRIPTION:

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical wall mounting or installation on floor, in vertical or in horizontal position (optional*). **Manufactured in STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Tank includes brackets for wall mounting, sensor pocket on upper connections plate and thermometer on top cover.

MAIN CHARACTERISTICS

Total capacity:	Total / DHW Tank	130 / 100	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	1.2	m ²
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	50	W
External dimensions:	D: Diameter	480	mm
	H: Height (without connections)	1155	mm
	Diagonal (without connections)	1251	mm
Packaging dimensions:	Width / Height	500 / 1370	mm
Weight:	Without packaging / With packaging	45 / 52	kg

(*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.