



PRODUCT TECHNICAL SPECIFICATION  
GEISER INOX – **GX6S90**

FCP\_01\_01\_EN



**DESCRIPTION:**

“**DOUBLE WALL**” tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical wall mounting or installation on floor, in vertical or in horizontal position (optional\*). **Manufactured in STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Tank includes brackets for wall mounting, sensor pocket on upper connections plate and thermometer on top cover.

**MAIN CHARACTERISTICS**

Total capacity:	Total / DHW Tank	82 / 62	L
Maximum working pressure:	Primary / Secondary	3 / 8	bar
Maximum working temperature:	Primary / Secondary	110 / 90	°C
Exchange surface:	DHW tank wall	0.8	m <sup>2</sup>
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	¾	" M
	kw: cold water inlet / drain	¾	" M
	z: recirculation	¾	" M
Energy efficiency:	ErP Class	B	
	Static heat losses acc. to EN12897	45	W
External dimensions:	D: Diameter	480	mm
	H: Height (without connections)	750	mm
	Diagonal (without connections)	890	mm
Packaging dimensions:	Width / Height	500 / 970	mm
Weight:	Without packaging / With packaging	35 / 40	kg

(\*) For horizontal installation, the tank is supplied with a specific secondary hydraulic connections plate (DHW), for right or left horizontal orientation, factory mounted.