



PRODUCT TECHNICAL SPECIFICATION  
LARGE CAPACITIES – **MXV10000RB**

FCP\_019\_03\_EN-01



**DESCRIPTION:**

Tank for domestic hot water (DHW) **STORAGE**.

For vertical installation on floor. Made of **STAINLESS STEEL AISI 316**, chemically pickled and passivated.

Equipped with DN400 side manhole for inspection / cleaning tasks, or optionally, for the installation of a stainless steel plate to allocate electric heating elements.

Optional: PVC lining along with 50 or 100 mm thick glass fibre thermal insulation, supplied in separate packaging.

Optional: ALUNOX lining along with 80 mm PU or 100 mm rock wool thermal insulation, supplied factory fitted.

**MAIN CHARACTERISTICS**

Total capacity:	Total	10000	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	kw/e: cold water inlet / drain	3	" M
	ww: DHW outlet	3	" M
	z: recirculation	1 ½	" M
	R: side connection for electric element	2	" F
	pc: lapesa "Correx-up" connection	¾	" F
	tm: sensor connection	½	" F
External dimensions:	D: Diameter	1750	mm
	H: Height (without connections)	4808	mm
	Diagonal (without connections)	5116	mm
Weight:	Without packaging	887	kg