



TECHNICAL PRODUCT SPECIFICATION
MASTER INERTIA – MXV4-3500IB

FCP_061_05_EN



DESCRIPTION:

Stainless steel **BUFFER TANK**, for closed heating and cooling circuits. Manufactured in **STAINLESS STEEL AISI 304**. For vertical installation on floor. Tank includes rigid mould-injected **PU thermal insulation**. Optionally, a kit of external padded PVC lining, to be supplied in separate packaging unmounted. Tank also includes one side threaded connection for an optional electrical heating element. Equipped with DN400 side manhole for inspection / cleaning tasks.

MAIN CHARACTERISTICS

Total capacity:	Total	3500	L
Maximum working pressure:		6	bar
Maximum working temperature:		110	°C
Connections:	s: side connection	4	" F
	p: upper connection	2	" F
	eh: side connection for electric element	2	" F
	e: drain connection	1	" M
	tm: sensor connections	½	" F
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	232	W
External dimensions:	D: Diameter	1660	mm
	H: Height (without connections)	2580	mm
	Diagonal (without connections)	3067	mm
Packaging dimensions:	Width / Height	1660 x 2600	mm
Weight:	Without packaging / With packaging	527 / 528	kg