



TECHNICAL PRODUCT SPECIFICATION
MASTER INERTIA – MXV4-6000IB

FCP_061_08_EN-01



DESCRIPTION:

Stainless steel **BUFFER TANK**, for closed heating and cooling circuits. Manufactured in **STAINLESS STEEL AISI 304**. For vertical installation on floor. Tank includes rigid mould-injected **PU thermal insulation**. Optionally, a kit of external padded PVC lining, to be supplied in separate packaging unmounted. Tank also includes one side threaded connection for an optional electrical heating element. Equipped with DN400 side manhole for inspection / cleaning tasks.

MAIN CHARACTERISTICS			
Total capacity:	Total	6000	L
Maximum working pressure:		6	bar
Maximum working temperature:		110	°C
Connections:	s: side connection	4	" F
	p: upper connection	2	" F
	eh: side connection for electric element	2	" F
	e: drain connection	1	" M
	tm: sensor connections	½	" F
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	280	W
External dimensions:	D: Diameter	1910	mm
	H: Height (without connections)	3210	mm
	Diagonal (without connections)	3735	mm
Packaging dimensions:	Width / Height	1910 x 3250	mm
Weight:	Without packaging / With packaging	952 / 953	kg