



PRODUCT TECHNICAL SPECIFICATION
MASTER INOX – MXV3500RB

FCP_018_05_EN



DESCRIPTION:

Tank for domestic hot water (DHW) **STORAGE**.

For vertical installation on floor. Manufactured in **STAINLESS STEEL AISI 316**, chemically pickled and passivated, with mould-injected rigid **PU thermal insulation**. As option, external PVC lining, to be supplied in separate packaging.

Equipped with DN400 side manhole for inspection / cleaning tasks, or optionally, for the installation of a stainless steel plate to allocate electric heating elements.

MAIN CHARACTERISTICS

Total capacity:	Total	3500	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	ww: DHW outlet	3	" M
	kw: cold water inlet	3	" M
	z: recirculation	2	" M
	e: drain	1	" M
	R: side connection for electric element	2	" F
	pc: "lapesa correx-up" connection	¾	" F
	tm: sensor connection	½	" F
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	232	W
External dimensions:	D: Diameter	1660	mm
	H: Height (without connections)	2580	mm
	Diagonal (without connections)	3067	mm
Packaging dimensions:	Width / Height	1660 x 2600	mm
Weight:	Without packaging / With packaging	520 / 520.5	kg